

## Hal Single End 64656 HLX

Low-voltage halogen lamps without reflector



### Areas of application

- Lamps for special luminaires
- Medical fiber optics (HLX)

### Product benefits

- Compared to standard lamps up to 10 % higher luminous efficacy (HLX)
- Instant light (HLX)

### Product features

- Xenon instead of krypton as the filler gas (XENOPHOT HLX versions)
- Luminous flux up to 10 % higher with same power consumption (XENOPHOT HLX versions)
- HLX tungsten halogen low-voltage lamp with or without reflector
- Dimmable (HLX)



## Product datasheet

---

### Technical data

#### Electrical data

Nominal voltage	24.0 V
Nominal wattage	275.00 W

#### Photometrical data

Color temperature	3550 K
Nominal luminous flux	10000 lm

#### Dimensions & weight

Diameter	13.5 mm
Length	55.0 mm
Light center length (LCL)	33.0 mm
Filament length	7.00 mm
Illuminated field	7.0*3.5 mm <sup>2</sup>
Filament diameter	3.5 mm

#### Lifespan

Lifespan	75 h
----------	------

#### Additional product data

Base (standard designation)	G6.35
-----------------------------	-------

#### Capabilities

Burning position	s90
------------------	-----

#### Certificates & standards

EEL – Energy Label	B
--------------------	---

#### Country specific categorizations


ANSI code	FNT
Order reference	64656 HLX

---

### Country specific information

Product code	METEL code	SEG-No.	STK number	UK Org
4050300023120	OSRH6465640	-	4736556	-

## Product datasheet



### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300023120	Hal Single End 64656 HLX	Folding carton box 1	25 mm x 23 mm x 70 mm	0.04 dm <sup>3</sup>	5.34 g
4050300890777	Hal Single End 64656 HLX	Shipping carton box 40	144 mm x 107 mm x 121 mm	1.86 dm <sup>3</sup>	254.60 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.