

USB3.0 4CH/2CH AHD 視頻外接擷取卡產品規格

產品特性

- 4 路 AHD/2 路 AHD 視頻信號輸入
- 輸入視頻信號:720P 四路/1080P 兩路 (選配)
- UVC 相容視頻擷取 · YUV422 視頻輸出
- Windows 作業系統 Mac OS 作業系統, Linux 作業系統
- 無需安裝驅動 · 真正的 PnP
- 超低功耗 · 無需外接電源適配器 · 直接 USB 供電
- 尺寸 : 80x74x24mm

高級特性

- USB3.0 時 5Gb/s 傳輸帶寬
 - 視頻處理由擷取卡完成 · 不佔用主機 CPU
 - 自動判斷輸入視頻格式 · 並自動變換至指定的輸出大小
- USB3.0 輸出 : 1280X720/1920X1080
- USB2.0 輸出 : 480X270(AHD 1080P),640X360(AHD 720P)
- 亮度、對比度、色調、飽和度等畫面調節功能。
 - 支持一機多卡。
 - 固件可升級。

Features

- 1)4CH AHD video input
- 2)Video signal input:720P
- 3)UVC compatible video capture,YUV422 video output
- 4)Windows & Mac OS & Linux OS & Andriod supported
- 5)P&P,no driver
- 6)Ultra low power consumption,no adapter ,power over USB

Advanced Feature

- 1)USB3.0@5Gb/s bandwidth
- 2)Video captured by USB device, Low CUP occupancy rate
- 3)Video format auto Detection :
USB3.0 output:
1920X1080/1280X720
- 4)Brightness,Contrast,Hue,Saturability adjustable.
- 5)One video for multi capture device

Application

1. IPTV (Wowza, Xtream Codes, etc.,)
2. Online Live Broadcast
3. NVR (Net Video Recorder)
4. Teaching / Campus Broadcast
5. Hotel TV system
6. Video Conference
7. Digital Signage
8. Recording System

Specifications

| | |
|--------------|------------------------|
| Connectivity | |
| Interface | USB3.0,5Gb/s bandwidth |

| | |
|---------------------|--|
| Video Interface | BNC |
| AHD Video Input | 2 CH AHD Video signal |
| Standard | |
| AHD Input Format | AHD 720P /1080P |
| Bite rate | 5Gb/s |
| Video Capture | compliance with UVC (USB video class) |
| Audio Capture | No |
| Output Color | YUY2 |
| Others | |
| OS | Windows XP/7/8.1/10,Mac OS,Linux |
| Software | Windows Media Encoder, Adobe Flash Media Live Encoder, Real Producer Plus, VLC, Wirecast VMIX... |
| | |
| API | DirectShow (Windows),UVC API |
| Dimention | |
| Power consumption | <= 1.0 W |
| Work Temperature | 0-50 degree centigrade |
| Storage Temperature | -20-70 degree centigrade |
| Storage humidity | 5%-90% |