

1510

Protector

Carry-On Case

The original case introduced over 45 years ago has since evolved into the global standard for equipment protection. The Protector Case series is designed to survive and trusted to travel to the harshest environments on earth.

The Pelican 1510 Protector Case provides military-grade protection for a wide variety of gear, from camera equipment to camping kits. It is available with foam, without foam, padded dividers, or TrekPak dividers. The Pelican 1510 Protector Case is the maximum airline carry-on size, so you can travel with your sensitive gear close at hand.

- Personalized nameplate service available
- Maximum airline carry on size*
- · Strong polyurethane wheels with stainless steel bearings
- · Watertight, crushproof, and dustproof
- Automatic pressure equalization valve balances interior pressure, keeps water out
- Comfortable rubber over-molded top and side handles
- Easy open double-throw latches
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Retractable extension trolley handle
- Stainless steel hardware and padlock protectors
- * Check with your airline for exact measurement requirements.



CONFIGURATIONS



1510 Standard



1514 With Padded Dividers



1510NF



1510TP With TrekPak Divider System



1510WF With Foam



1510TPF TrekPak / Foam Hybrid

DIMENSIONS

Interior (L×W×D) 19.75 x 11.00" x 7.60 (50.2 x 27.9 x 19.3 cm) Exterior (L×W×D) 22.00 x 13.81" x 9.00 (55.9 x 35.1 x 22.9 cm)

 Lid Depth
 1.79" (4.5 cm)

 Bottom Depth
 5.79" (14.7 cm)

 Total Depth
 7.58" (19.3 cm)

 Int Volume
 0.96 ft³ (0.027 m³)

 Padlock Hole Diameter
 0.31" (0.8 cm)

MATERIALS

Body Polypropylene

LatchABSO-RingPolymerPinsStainless SteelFoam1.3 lb Polyurethane

Purge Body ABS

Purge Vent 3 Micron Hydrophobic Non-Woven

COLORS

Black Desert Tan OD Green

WEIGHT

Weight With Foam 13.60 lbs (6.2 kg)
Weight Empty 11.99 lbs (5.4 kg)
Buoyancy 64.15 lbs (29.1 kg)
Weight With TrekPak / Foam Hybrid 14.94 lbs (6.8 kg)
Master Pack Weight 32.43 lbs (14.7 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C) **Maximum Temperature** 210°F (98.9 °C)

CERTIFICATIONS

IP67

Def Stan 81-41

OTHER

Wheels 2
Extendable Handle yes
Master Pack 2
Nameplate yes
Reduced Area yes
Military yes

ACCESSORIES



4 pc. Replacement Foam Set



1513 Replacement O-ring



1515 Padded Divider Set



1519 Lid Organizer



1510TPKIT TrekPak Case Divider Kit



1510TPDIV Extra TrekPak Dividers



1507 Quick Mounts - set of 4



1506TSA TSA Lock



1500D Desiccant Silica Gel



1510MP EZ-Click™ MOLLE Panel



Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 <u>sales@pelican.com</u> • <u>www.pelican.com</u>

Document created on 11-24-23