

導播機

4K 8通道導播機**SE-4000**

影像系統	4K & HD
影像格式	<p>Input: 3840x2160p: 60/59.94/50/30/29.97/25/24/23.98 1080p: 60/59.94/50/30/29.97/25/24/23.98 1080i: 60/59.94/50, 720p: 60/59.94/50 VGA, XGA (1024 x 768), SXGA (1280 x 1024), UXGA (1600 x 1200), WUXGA (1920 x 1200)</p> <p>Output: 3840x2160p: 60/59.94/50/30/29.97/25/24/23.98 1080p: 60/59.94/50/30/29.97/25/24/23.98 1080i: 60/59.94/50, 720p: 60/59.94/50</p>
影像處理	SDI: 4:2:2 10-bit HDMI: YUV 4:2:2 10-bit, RGB: 4:4:4 8/10-bit
輸入設定	YES
影像輸入	Total 8 live inputs (select 8 from 12) 8 x 12G-SDI 4 x HDMI
相容HD/SD	----
電腦連結	4 via HDMI
影像輸出	4 x 12G-SDI 3 x HDMI All assignable: Multiview, PGM, PVW, PGM+DSK, Clean PGM, Clean PVW, Input 1-12
下轉輸出	----
多分割監看	HDMI & SDI assignable
聲音輸入	4 x Analogue XLR
聲音輸出	2 x Analogue XLR
支持聲音軌數	Input 4 channels, Output 4 channels
聲音延遲	Up to 16 fields or 8 frames per channel
影音像同步切換	Yes
影像去背	4
字幕機	Yes, CG-200 software free download
USK	4x Keyer support Chromakey/ Linear/ Luma Key
DSK	2x DSK support Lumakey & Linear key (Key / Fill)
子母畫面	2
LOGO顯示	2
圖片顯示	999+
特效	DVE, FTB, Cut, 32 Wipe with border
過場預覽	Full transitions preview

同步訊號輸入/出	Built-in Genlock Support external sync with loop thru
Tally輸出	1x D-sub 25pin, dual color
電腦控制	DVIP (Ethernet)
Camera Control	----
混音器	----
Storage	----
Recording File System	----
Recording File Format	----
Video Encode	----
Audio Encode	----
Streaming Protocol	----
Firmware Update	Ethernet
特別功能	5" Touchscreen Display
外型	2 units, 2RU rack-mount mainframe
尺寸	433 x 312 x 76 mm (switcher) 432 x 252 x 88 mm (main unit)
重量	7.1 kg
電源	DC 12V, 108W
操作溫度	0~40 °C
附件	1 x SE-4000 Main Unit 1 x SE-4000 Control Board 2 x AD Switch DC 12V 2 x AC Cord 1 x Ethernet Cable 12 x Screw 2 x 2U Ear Rack